

Interference Search

EAST Search History

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	0	(infrared heater comprised of two sets of parallel electrically-resistive bars the corresponding bars of the respective sets being juxtaposed-electric conductors interconnecting corresponding ends of the bars and connectors for applying "180" degrees out of phase electrical current to the respective sets of conductors that current flows in directions in corresponding bars at any given point in time and a protrusioned infrared source comprised of a base adapted to be heated and protrusions which project away from the base and present comfortable touch finned and has valleys between the fins, and the valleys overlies corresponding electrically-resistive bars).clm.	US-PGPUB; USPAT	AND	OFF	2006/08/03 09:49
L2	0	(infrared heater comprised of two sets of parallel electrically-resistive bars the corresponding bars of the respective sets being juxtaposed-electric conductors interconnecting corresponding ends of the bars and connectors for applying "180" degrees out of phase electrical current to the respective sets of conductors that current flows in directions in corresponding bars at any given point in time and a protrusioned infrared source comprised of a base adapted to be heated and protrusions which project away from the base and present comfortable touch finned and has valleys between the fins, and the valleys overlies corresponding electrically-resistive bars).clm.	US-PGPUB; USPAT	AND	OFF	2006/08/03 09:49